

GENERAL INFORMATION:

- A special effect decorative paint based on Acrylic emulsion resin.
- Suitable both for unique home styling and public areas such as hotels, restaurants, offices and more.
- Decorative effect for exterior walls.
- **Suede GSU** base: sparkling metallic look.
- **Suede MSU** base: light sparkling metallic look.



FEATURES:

- ✓ Odorless.
- ✓ Sparkling metallic effect with Suede-like finish.
- ✓ Effects changes as a result of the angle, lightning and application.
- ✓ Matt & sparkling finish.
- ✓ Ready to use – not dilute.

CERTIFICATION:

- ✓ Quality Management ISO9001.
- ✓ Environment Management ISO14001.
- ✓ Health & Safety management OEHSA ISO18001.

TECHNICAL DATA:

Binder type:	Acrylic emulsion	Color shade:	Tambour color collection
Solid content by volume:	61.3%	Humidity limit:	Less than 85%
Solid content by weight:	70.4%	Application temperature:	Min: 10°C Max: 40°C
PH value:	8.5	Drying time:	Touching(*): 1 hour Re-coat: 3 hours Full dry: 72 hours
Thinner:	NA	Drying method:	Evaporation & Coalescence
Viscosity:	85-95	Calculated coverage (**):	2-3 m ² /l (in 3 coats)
Density:	1.00-1.10 g/cm ³	Gloss:	Matt
Packsize:	3l		
Storage:	below 30°C		
Shelf-life:	2 years		

Free of lead and Chromates. Product is not self-igniting and not present an explosion hazard.

** At 25°C and 65% humidity. ** The actual coverage rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage ability.*

SURFACE PREPARATION:

The effect can be applied on any wall that covered with acrylic paint. If the surface is painted with lime paint, then apply one coat of Tambour recommended before applying the acrylic paint. Best used in accordance with the attached instruction booklet. Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2.

Notice: To achieve maximum results and successful effect, the wall intended for painting must be smooth, without textures or flaws.

APPLICATION GUIDE:

To achieve full coverage and an easy and fast work, apply two coats of **Suede** using a dry shorthaired roller. Wait for about two hours between the coats. To obtain the final look, apply another coat using a brush. The final color, especially the shade depends on the number of layers applied and the amount of paint used on the brush. The lighter the selected color, the gentler the cloudiness. The cloudiness shall be more visible in shaded areas.

Applying the effect coat (the third coat): Dip a brush (3" – 4" wide) in the paint container. Remove excess paint from the brush. Apply the paint on the wall in wide crisscross [X] movements. Continue painting and blur boundaries so that individual diagonal lines are not visible. It is recommended to apply over a diagonal section of about 0.5-1 sqm at a time, and ensure complete coverage (very important). It is recommended to step away from the wall occasionally during the application, to view the entire wall. The final look of the **Suede** effect shall be obtained after three coats and upon full drying.

SAFETY INFORMATION:

Cleanup and Storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

Cautions: The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

General Notes: Do not apply when the wall is wet or when it is expected to rain before or after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. For cracked walls use the Tambourflex Paint System. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared and suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.