

GENERAL INFORMATION:

- High quality primer with solvent based Acrylic.
- Exterior application.
- Suitable for plastered wall, concrete, masonry, brick, MDF.



FEATURES:

- ✓ Excellent adhesion on various surface.
- ✓ Matt and flat finish.
- ✓ Anti-stain.
- ✓ Good alkali resistance.
- ✓ White color.

CERTIFICATION:

- ✓ Quality Management ISO9001.
- ✓ Environment Management ISO14001
- ✓ Health & Safety management OEHS ISO18001.

TECHNICAL DATA:

Binder type:	Solvent based Acrylic	Color shade:	White
Solid by volume:	47.70%	Humidity limit:	less than 85%
Solid by weight:	59.80%	Application temperature:	Min: 10°C Max: 40°C
PH value:	NA	Drying time:	Touch dry(*): 1 hour Re-coat: 4 hours Full dry: 72 hours
Thinner:	White spirit	Drying method:	Evaporation & Coalescence
Density:	1.25-1.31 g/cm ³	Calculated coverage (**):	10 m ² /l (in 1 coats)
VOCs:	9.15%	Dry film thickness:	40µm
Packsize:	5l, 18l		
Storage:	below 30°C		
Shelf-life	2 years		

Free of Lead and Chromates. Product is not self-igniting and not present an explosion hazard.

* At 25°C and 65% humidity.

** The actual coverage rate can vary, depending on the substrate condition, the application method, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated coverage.

SURFACE PREPARATION AND SYSTEM RECOMMENDATION:

Make sure that the surface was prepared in accordance with IS 1920 part 1 and 2. Remove any old, loose and peeling paint. Clean the wall with a water jet in a pressure of 120atm. Repair any concrete and plaster defects as needed (For new concrete, primer can be applied only after the concrete is completely cured, about one month after application). Apply **Tambourflex Adhesion primer** using a brush or roller. Allow drying for 4 hours before applying Tambour Paint System or any other topcoat. Do not apply the **Tambourflex Adhesion Primer** and leave it uncoated for more than a week.

APPLICATION GUIDE:

Application: Stir the paint well before application to obtain a uniform mixture. Roller/ Spray (Airless) Application: Dilute the primer with up to 30% of Tambour Mineral White Spirit.

SAFETY INFORMATION:

Cleanup and Storage: Clean work tools with soap and water immediately after use. Close the container tightly to prevent air penetration. Store in a roofed and ventilated place, below 30°C.

Cautions: The paint is inedible, the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children. Use in a well ventilated area only. Specific information regarding the product is available in the safety manual (MSDS).

General Notes: Do not apply when the wall is wet or when it is expected to rain before or after the application and/or the wall temperature is below 10°C and the relative humidity is above 85%. For cracked walls use the Tambourflex Paint System. Do not mix this product with products not recommended by us. Achieving desired results is dependent on the proper application of the product while following all instructions. Before applying the product, the user must make sure that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared and suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or change it at our discretion.

Manufactured by Tambour, a company with a quality assurance system that meeting the requirements of Israeli Standards ISO 9001, ISO 18001, ISO 14001 and accredited by the Israel Institute of Standards in compliance with them.